



Gator Dust polymeric stone dust

IDEAL FOR

- NATURAL STONE PATIOS
- NATURAL STONE WALKWAYS
- PATHWAYS
- YOU DON'T HAVE TO BE AN EXPERT TO GET PROFESSIONAL RESULTS
- SWEEP IT IN THE JOINTS, SPRAY A MIST OF WATER AND YOU'RE DONE
- AVAILABLE IN STONE GREY & SAHARA BEIGE FOR JOINTS .5" TO 4"

ADVANTAGES OVER CEMENT JOINTS:

- SWEEP POLYMERIC DUST IN JOINTS (NO TROWELLING)
- NATURAL STONE FINISH ON SURFACE (UNLIKE WHITE CEMENT JOINT)

Polymeric Stone Dust is recommended for a variety of uses, including pool sides, patios, foot paths, etc... Natural stones have to be installed on drainage bed systems: maximum of 1" (2.5 cm) of sand or stone dust, plus a minimum of 5" (12.5 cm) of crushed stone.

GATOR DUST COVERAGE

The quantity required depends on the shape and size of the natural stones as well as the width of the joints. 22.7 kg (50 lbs) of this product will cover between 1.86 and 2.79 square meters (20 to 30 square feet) if the joints are about 2.5 to 5 cm (1" to 2") wide and the natural stones are about 5 to 6 cm (2" to 2-1/2") thick.

PLEASE NOTE

Gator Dust Bond hardens like concrete and will crack if the crushed stone base has movement. NEVER USE POLYMERIC STONE DUST WHEN PAVERS ARE INSTALLED ON A CONCRETE SLAB. GATOR DUST BOND MIGHT LEAVE A WHITE RESIDUE IF USED ON CONCRETE PRODUCTS.

INSTALLATION

1. Install natural stones on crushed stone bedding that is well compacted.
2. Sweep Gator Dust Bond in between the natural stone joints.
3. Hit the natural stones with a rubber hammer; this will make Gator Dust settle firmly into the joints by removing air pockets.
4. Sweep off all excess Gator Dust on the natural stone surface. Ensure that Gator Dust lies 3mm (1/8") below the top of the paver (repeat step 3 if necessary).
5. Direct a fine mist of water in the air to dampen all the Gator Dust joints. Dampen until there is water retention on joints surface (45 seconds).
6. Minimize or avoid, if possible, walking on the natural stones for 24 hours after the installation of Gator Dust.

FEATURES

- PRODUCT WORKS AT ABOVE 15°C (59°F)
- COMPATIBLE WITH ALL TYPES OF NATURAL STONES
- GATOR DUST BOND IS IDEAL FOR JOINTS THAT ARE A MINIMUM OF 9.5MM (3/8") TO A MAXIMUM OF 100MM (4") WIDE

POLYMERIC STONE DUST FOR NATURAL STONE

IDEAL FOR

- NATURAL STONE PATIOS
- NATURAL STONE WALKWAYS
- PATHWAYS

ADANTAGES OVER CIMENT JOINTS

- SWEEP GATOR DUST IN JOINTS (NO TROWELLING)
- NATURAL STONE FINISH ON SURFACE (UNLIKE WHITE CEMENT JOINT)

FOR JOINTS 1/2" TO 4"



- NEW COLOR
- SAHARA BEIGE
- STONE GREY

